

A NEW B1-rated fire resistant Aluminium Composite Panel with a revolutionary core material

JEN

AlupanelFR is a high quality panel with a specially formulated halogen-free core material designed to offer enhanced fire resistance whilst retaining excellent fabrication characteristics and outstanding adhesion strength.

Innovative core material

The specially formulated core material used in AlupanelFR provides many advantages over alternative products whilst retaining the many features that are essential to the demands of today's fabricators.

Versatile & easily formable

AlupanelFR can be rolled, folded and formed extremely easily. Test results show excellent flexibility with a combination of exceptional strength, allowing numerous fabrication options with no risk to the physical integrity of the panel.

Machines easily with minimal tool wear

AlupanelFR machines much more quickly and with significantly less wear to the cutting tools, saving fabricators both time and money.

Lightweight yet rigid

Thanks to the specially formulated core, AlupanelFR is considerably lighter than other fire resistant panels, making it much easier to transport and handle but with no compromise to the rigidity of the panel.



Our product development team have worked tirelessly to develop a panel that offers our customers a product that is suitable for an immense variety of applications, including environments where improved fire classification is required, but without sacrificing build quality.

Lighter than many fire-resistant Aluminium Composite Panels, AlupanelFR not only fabricates extremely well but machining is much faster than comparable products and with minimal wear on machine tools unusual for a fire resistant panel.



| Property | |
|--------------------------------------|----------------|
| Panel Thickness (mm) | 3 |
| Skin Thickness (mm) | 0.3 |
| Weight (kg/m²) | 4.3 |
| Skin | Gloss / Matt |
| Core composition | Fire Retardant |
| Bond integrity (N/mm) | 7.001 |
| Bending modulus (N/mm ²) | 17374.885 |
| Train at break (%) | 4.215 |
| Fire classification (EN13501-1) | B - s1 , d0 |



Corporate ID

Interior wall and ceiling decoration Modular/Offsite construction Sports arenas Airports, railway stations Vehicles, trains & boats Shopping centres Hospitals Sign-making Splashbacks Machine casings



Paint finish Available in a wide range of colours and finishes

Easy-peel protective film designed to protect the panel

| Standard sheet sizes | | |
|----------------------|-------------|--|
| Width | Length | |
| 1220 | 2440 / 3050 | |
| 1500 | 3050 / 4050 | |



Available from all Perspex Distribution Branches **BLACKBURN:** LEEDS: WEYBRIDGE:

01254 272 800 01134 677 800 01932 356 900

CHELMSFORD: TAMWORTH:

01245 232 800 01827 263 900