

# Transprint 3 Matt Overlaminat

## Face Material

Matt clear monomeric soft vinyl.

Type	Monomeric vinyl	
Colour and Finish	Matt clear	
Weight	93 g/m <sup>2</sup> ±10%	ISO-536
Thickness	70 µ ±10%	ISO 534-80

## Adhesive

Solvent based permanent acrylic adhesive featuring good water and high UV resistance. Designed for overlamination and mounting applications.

Reference	ASP5 permanent	
Type	Acrylic permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-40°C/+120°C	
Shear	Medium	
Tack	Medium N/inch <sup>2</sup>	
Final Adhesion	High N/inch	

## Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m <sup>2</sup> ±10%	ISO 536
Thickness	55 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

## Applications

For difficult surfaces requiring conformability and UV protection.

## Printing Methods

Not printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

## Shelf life

36 months, applicable only to the material delivered by Transprint which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

*All products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.*

# TRANSPRINT

www.perspex.co.uk