

Transprint Mesh Banner

Base Fabric	(DIN 60001)	Trade Mark Polyester
Warp/Weft		1100 D-tex
Threads (per inch)	(DIN 53853)	12/12
Total Weight	(DIN 53352)	280-310 grs/m2 Base fabric 120g/m2 ca)
Tensile Strength warp/weft	(DIN 53354)	1500/1400 N/5cm (171/160 Lb)
Tear Resistance warp/weft	(DIN 53363)	250/350 N/5cm (56/79 Lb)
Width		Up to 320cm with liner Up to 500cm without liner
Temperature Resistance	(DIN 53372)	-10°C – 60°C
Application		Solvent Ink Printing
Coating		PVC coated on both sides
Flame Retardant	(DIN 75200)	Self-extinguishing <i>Standard Version</i>
Flame Resistance	(DIN 4102)	Complies with B1 <i>THE FR VERSION</i>
Opening Percentage		Approx 19%
Permeability of Light		Approx 43%
Air permeability		Approx 1.650 L / m2 / sec

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall Transprint be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet. All vinyls are sold subject to our Conditions of Sales/Notice to Purchaser. Transprint also retains the right to change sizes and specifications of products without prior notice.

***The buyer will test the products before actual use and shall determine the suitability of the product for its intended purpose and the user assumes all risk and liability whatsoever, in connection therewith.**

***Under no circumstances, Transprint shall be liable for any loss, damage, expense or consequential damages of any kind arising from the use or inability to use Transprint products.**

Premium dipped Mesh membrane for general poster & billboard and building wrap production use with solvent & UV curable ink.

All products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

TRANSPRINT

www.perspex.co.uk