

Transprint Semi-Coated Banner

Base Fabric	(DIN 60001)	Trade Mark Polyester
Yarn W/F	(DIN 53830)	1100/1100 dtex
Thickness	(DIN 53352)	0.55mm +/-
Weave	(DIN 61101)	L1/1
Threads (W/F per cm)	(DIN 53853)	7/7 (18/18)
Basecloth Weight	(DIN 53854)	160 g/m2 +/- 4oz/yd.sq +/-
Total Weight	(DIN 53352)	450 grs/m2 +/-10grs
Tensile Strength	(DIN 53354)	2340/2117 N/5cm 267/240 lb/in
Tear Resistance warp/weft	(DIN 53363)	294/225 N 30/27 Kgs/5cm
Adhesion	(DIN 53357)	70 N/5cms 7Kgs/5cm
Flex-Resistance	(DIN 53359)	100,000 bends +/-
Cold Resistance	(DIN 53361)	-20°C+ 0 +70 °C
Application		Frontlit Inkjet Printing/Billboard (Eco)
Flame Retardant	(DIN 75200)	Self Extinguishing Non FR Version
Flame Resistance	(DIN 4102)	B1
Shearin Resistance	(DIN 53354)	2cm overlap seaming joint

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall Transprint be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet. All Transprint vinyls are sold subject to our Conditions of Sales/Notice to Purchaser. Transprint also retains the right to change sizes and specifications of products without prior notice.

***The buyer will test the products before actual use and shall determine the suitability of the product for its intended purpose and the user assumes all risk and liability whatsoever, in connection therewith.**

***Under no circumstances, Transprint shall be liable for any loss, damage, expense or consequential damages of any kind arising from the use or inability to use Transprint products.**

Premium quality **semi-coated** Frontlit material for general use in the production of latex, solvent & UV curable ink print Superwide graphics / Billboards. (Short-term to Mid Term) shelf life 6 months.

All products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

TRANSPRINT

www.perspex.co.uk